

PRODUCT DATA SHEET

Eberspächer Airtronic L D5 12V & 24V

12V - 25.2361 24V - 25.2362



TECHNICAL DATA



HEATER TYPE	Airtronic						
HEATER	Airtronic L						
VERSION	D5						
HEATING MEDIUM	Air						
FUEL	Diesel – standard commercially available (EN 590)						
CONTROL OF THE HEAT FLOW		POWER	HIGH	MEDIUM	LOW	OFF	
HEAT FLOW (WATT)		5500	4800	2700	1600	–	
HOT AIR THROUGHPUT WITHOUT BACKPRESSURE (KG/H)		280	275	190	155	–	
HEATER CODE		10					
FUEL CONSUMPTION (L/H)		0.66	0.58	0.34	0.20	–	
AVERAGE ELECTRICAL POWER CONSUMPTION (WATT)		during operation	85	80	35	25	–
		while starting	≤ 250				
RATED VOLTAGE		12 volt or 24 volt					
OPERATING RANGE	LOWER VOLTAGE LIMIT:		approx. 10.5 volt or approx. 21 volt				
	UNDERVOLTAGE PROTECTION INSTALLED IN THE CONTROL BOX SWITCHES OFF THE HEATER ON REACHING THE VOLTAGE LIMIT.		Undervoltage protection trigger time: 20 seconds				
	UPPER VOLTAGE LIMIT:		approx. 16 volt or approx. 32 volt				
	OVERVOLTAGE PROTECTION INSTALLED IN THE CONTROL BOX SWITCHES OFF THE HEATER ON REACHING THE VOLTAGE LIMIT.		Overvoltage protection trigger time: 20 seconds				
AMBIENT TEMPERATURE	Heater	during operation	–40 °C to +70 °C				
		not in operation	–40 °C to +85 °C				
	Metering pump	during operation	–40 °C to +50 °C				
		not in operation	–40 °C to +85 °C				
HOT AIR INTAKE TEMPERATURE		+40 °C					
INTERFERENCE SUPPRESSION		Interference suppression class 5 to DIN EN 55 025					
WEIGHT		approx. 9.3 kg					
VENTILATION MODE		possible					

Provided no other values are given, the technical data provided is with the usual tolerances of ±10 % at rated voltage, 20 °C ambient temperature and reference altitude Esslingen.

